



# How to safely secure your MCL Megalock security seal to a shipping container

## OBJECTIVE

- ⚠️ Secure both the left and right-side doors with all seal numbers and bar-codes facing out.

## RED SQUARE LOCKING BODY AND SECURITY CABLE

- ⚠️ Ensure numbers on the red locking body match the numbers on the bolt seal.
- ⚠️ Ensure all numbers are facing out and cable is pulled hand tight only.

*Please note that you may at times experience different container types. If so, the objective with the Megalock cable remains the same – securing both inside bars on each door.*

## Mega Fortris Limited

formerly Security Seals Limited

79 Titi Road, Mauku, Auckland 2678 NEW ZEALAND

Phone: +64 9 265 0262

Email: [admin@megafortris.co.nz](mailto:admin@megafortris.co.nz)

[www.megafortris.co.nz](http://www.megafortris.co.nz)



1

Install the bolt seal at the bottom of the right-hand door inside locking bar cam.



2

Feed cable over and under the inside bar on the left door, then back towards the inside bar on the right door.



3

Feed cable over and under the right-side inside bar and back towards the red square locking body.



4

Feed cable end through holes on red square locking body and gently pull hand tight.

**NOTE** ▶ Cable should end in a figure eight.

▶ Cable should be pulled firm however do not over tighten.

▶ Numbers on the bolt seal and red square locking body should be facing out.

## IMPORTANT MESSAGE

Please ensure to warn procurement when your security seal stock is getting low.